



Università degli Studi Mediterranea di Reggio Calabria
Archivio Istituzionale dei prodotti della ricerca

Comparison of Irrigation Management in Water User Associations of Italy, Spain and Turkey Using Benchmarking Techniques

This is the peer reviewed version of the following article:

Original

Comparison of Irrigation Management in Water User Associations of Italy, Spain and Turkey Using Benchmarking Techniques / Arslan, F., Tendero, J., Diaz, J., Zema, D.a.. - In: WATER RESOURCES MANAGEMENT. - ISSN 0920-4741. - 37:(2023), pp. 55-74. [10.1007/s11269-022-03355-2]

Availability:

This version is available at: <https://hdl.handle.net/20.500.12318/130769> since: 2024-11-22T10:25:11Z

Published

DOI: <http://doi.org/10.1007/s11269-022-03355-2>

The final published version is available online at: <https://link.springer.com/article/10.1007/s11269-022-03355-2>

Terms of use:

The terms and conditions for the reuse of this version of the manuscript are specified in the publishing policy. For all terms of use and more information see the publisher's website

Publisher copyright

This item was downloaded from IRIS Università Mediterranea di Reggio Calabria (<https://iris.unirc.it/>) When citing, please refer to the published version.

(Article begins on next page)

1 *This is the peer reviewed version of the following article:*
2

3 **Arslan F., Córcoles Tendero J.I., Rodríguez Díaz J.A., Zema D.A. 2023. *Comparison of***
4 ***Irrigation Management in Water User Associations of Italy, Spain and Turkey Using***
5 ***Benchmarking Techniques. Water Resources Management (Springer),***
6

7 *which has been published in final doi*
8

9 10.1007/s11269-022-03355-2
10

11 (<https://link.springer.com/article/10.1007/s11269-022-03355-2>)
12

13 *The terms and conditions for the reuse of this version of the manuscript are specified in the*
14 *publishing policy. For all terms of use and more information see the publisher's website*

Modelling the event-based hydrological response of olive groves on steep slopes and clayey soils under mulching and tillage management using the SCS-CN, Horton and USLE-family models

Giuseppe Bombino^(a), Pietro Denisi^(a,*), José Alfonso Gómez^(b), Demetrio Antonio Zema^(a), Santo Marcello Zimbone^(a)

^(a) *Mediterranea University of Reggio Calabria, Department "Agraria", Località Feo di Vito, I-89122 Reggio Calabria (Italy)*

^(b) *Institute for Sustainable Agriculture (IAS-CSIC), Agronomy Department, Avenida Menéndez Pidal s/n, E-14004 Córdoba (Spain)*

*Corresponding author: pietro.denisi@unirc.it

Abstract

The SCS-CN, Horton and USLE-family models are used worldwide, but few examples are available for olive groves on steep and clayey soils under mulching of pruning residues. We evaluate the accuracy in predicting runoff and soil loss of a steep (20%) and clayey olive grove subject to three soil conservation practices (SCPs): mechanical tillage (MT), mulching with pruning residues (NTR), and standard protection (SP), measured at plot scale in Southern Italy during 30 months under natural rainfall. The models were calibrated by adjusting the Curve Numbers (for the SCS-CN model), and the C-factors (MUSLE and USLE-M); the Horton model was not calibrated. The model performance was assessed by qualitative and quantitative procedures. In all practices, the SCS-CN was more accurate for runoff predictions (mean difference of 7% compared to corresponding observations) compared to the Horton (mean difference of 30%). For soil erosion, the MUSLE showed better performance in soils subject to mechanical tillage or total protection (differences lower than 10%), while the USLE-M was more reliable to simulate soil loss in mulched plots (differences of 8%). A set of Curve Numbers (95 for MT, 70 for SP, and 85 for NTR) and C-factors (0.4 for MT, 0.2 for SP, and 0.1 for NTR) are proposed for applications in steep slope and clayey soil olive orchards using the SCS-CN and USLE proposed models, respectively. Validation exercises in other environmental experimental conditions would enhance the export these models for runoff and erosion control in agricultural soils treated with mulching.

48

49 **Keywords:** *soil conservation; surface runoff; soil loss; pruning residue; SCS-CN model; USLE.*

50

51 **1. Introduction**

52

53 In Europe, sheet and rill erosion causes soil loss at a rate of almost 2.5 tons ha⁻¹ yr⁻¹, which is 1.6
54 times the soil formation rate (Panagos 2015). The assessment report on land degradation and
55 restoration (IPBES, Fisher et al., 2018) recommend “to increase efforts to reduce soil erosion and
56 increase soil organic matter and reduce agricultural areas with severe soil erosion rates (> 10 tons
57 ha⁻¹ yr⁻¹) by 2030” (Montanarella & Panagos 2021). Soil erosion rates in olive groves (*Olea*
58 *europaea* L.) in Southern Europe are estimated to have average soil losses of 95 tons ha⁻¹ yr⁻¹ over a
59 period of 50-100 years (Vanwalleghem et al., 2010).

60

61 In Italy, olives are often cultivated on steep slopes (sometime terraced), and these erosion rates can
62 be higher (Costantini and Dazzi 2013), which is exacerbated by specific climatic conditions (heavy
63 and infrequent storms with intense and often destructive floods, Fortugno et al., 2017; Zema et al.,
64 2018). Moreover, Italian olive groves in the past decades have been frequently abandoned, and this
65 has determined additional soil erosion, uneven landscape transformations and ecosystem
66 degradation (Ferrara et al., 2014; Pardini & Gispert 2013).

67

68 Reports (e.g. Gómez et al. 2014a; Polykretis et al., 2020) have shown that mechanical tillage
69 (Gomez et al, 2014a, 2017, 2018; Beaufoy, 2002; Xiloyannis et al., 2008) is often employed at
70 olive groves in order to improve nutrient levels (by incorporating fertilizer and organic matter into
71 the soil) and soil water balance (by reducing the soil evaporation), as well as to facilitate
72 harvesting. However, this practice, when intensive, may result in rapid oxidation of organic matter
73 (Kassam et al., 2009), worsening of the soil structure and thus increasing runoff and erosion rates,
74 particularly during wetter periods (Sastre et al., 2018). Due to frequent mechanical tillage coupled
75 with the absence of vegetative cover among trees, the current management of olive groves is highly
76 unsustainable and results in an average soil erosion rate of 23.2 tons ha⁻¹ yr⁻¹ (Vanwalleghem et al.,
77 2011). It is, therefore, important to control the hydrological response of olive groves, especially
78 when located on steep slopes or growing on clayey impervious soils.

79

Several hydrological models have been developed and used to predict water discharge and runoff, sediment transport and soil loss. These models are able to simulate the hydrological processes at the watershed and hillslope scale in a cost-effective and time-efficient way, helping land planners to identify the best practices for farmland management (Zema et al., 2020a).

More than twenty models to predict runoff and erosion are available and relevant applications have been globally carried out (Borrelli et al., 2021). Specifically, regarding erosion modelling, the USLE-family models are by far the most widely applied at the global scale with over 1200 applications. Other common erosion models are WEPP, LISEM, EROSION-3D, PESERA and EUROSEM, although applications of some of these models are decreasing (Bezak et al., 2021). Other models of common use are the Soil and Water Assessment Tool (SWAT, Arnold et al., 1998), AnnAGNPS (Bingner & Theurer, 2001), SEDD (Ferro and Porto, 2000), Water and Tillage Erosion Model, the Sediment Delivery Model (WaTEM/SEDEM, Van Oost et al., 2000), and the Morgan-Morgan-Finney ((R)MMF, Morgan et al., 1984). The SWAT, SEDD and AnnAGNPS models have been also used to predict erosion in olive groves (e.g., Zema et al 2016 for AnnGNPS application in a large Spanish watershed covered by olive groves, Massetti et al 2020, who simulated soil loss in olive groves using SWAT in central Italy, and Burguet et al 2012, who used the SEDD model in olive micro catchments of Spain).

Among the methods used to predict surface runoff, the Soil Conservation Service (SCS)-Curve Number (CN) (hereinafter “SCS-CN model”) is the most common for estimating runoff, (Mishra & Singh, 1999; 2013). The popularity of these methods is due to their simplicity, ease of use, widespread acceptance, and large availability of input data (Suresh Babu & Mishra, 2012; Soulis, 2021), thus the SCS-CN and USLE models are the hydrological and erosion components used in many catchments scale hydrological models. The prediction accuracy of the SCS-CN and USLE-family models has been verified in a large range of climatic and geomorphological conditions, with generally satisfying results. Reliable estimations of runoff and erosion can be gained if model calibration is carried out (Williams, 1977; Jackson et al., 1986; Michalec et al., 2017). However, examples of SCS-CN and USLE models calibrated for olive groves are few (Romero et al., 2007, Taguas et al., 2012; 2015b; Di Stefano et al., 2016; Nekhay et al., 2009).

In olive growing, soil conservation practices (hereinafter indicated as “SCPs”) are needed with the combined purposes of increasing crop productivity and protecting soil quality. Mulching and cover

crops with seeded or spontaneous species have been suggested and experimented for several years as SCPs. These innovative practices, if properly carried out, are beneficial for erosion reduction, water conservation and fertility maintenance. With regard to the hydrological impacts, several studies have demonstrated that mulching with pruning residues and cover crops are able to reduce the runoff and erosion rates under a wide range of climatic and morphological conditions (e.g., Gómez et al., 2011; 2014a; Gomez 2017; Bombino et al., 2019; 2021).

To consolidate the large use of conservative SCPs as anti-erosive practices, there is the need for more research to quantify of their hydrological impact. For this, the use of the hydrological models is reliable, easy and time-saving. Thanks to the hydrological models, the effectiveness of alternative SCPs can be predicted for a given environmental condition and this helps the task of land managers and olive farmers. Unfortunately, the studies that have applied the SCS-CN and USLE-family models to simulate the hydrological response of olive groves under different SCPs are limited in number, and therefore the literature shows several research gaps. To the best authors' knowledge, the prior applications of SCS-CN at plot scale have been carried out by Romero et al. (2007) and Mollenhauer et al. (2002), but none considered the SCP based on mulching of pruning residues in the lanes and their effects on steep slopes. Moreover, very few studies were carried out in similar environmental contexts as southern Italy with applications of different methods under variable spatial and temporal scales (Roskopf et al., 2020; Covelli et al., 2020).

For these purposes, this study evaluates the accuracy of the SCS-CN and Horton methods as well as two USLE-family models (MUSLE and USLE-M) to predict runoff and soil loss in a steep olive orchard in Calabria (Southern Italy) and subjected to different SCPs. More specifically, we hypothesize that some of these models are able to simulate surface runoff and soil erosion with more accuracy compared to the other models. The research questions to which this study aims to reply are the following: i) which is the dominant runoff generation mechanism (by saturation or infiltration excess) of the experimental soils? ii) to which process (rainsplash erosion or particle detachment and transport due to overland flow) is erosion due in the experimental conditions? iii) are all the tested models accurate for hydrological predictions under all the modelled SCPs? iv) what are the optimal CNs and C-factors values in the steep and clayey soils of olive groves in Southern Italy, to be integrated into the application guidelines of the studied models? The results of this study, to be further validated in other olive cultivation environments, could be a useful contribution for a broader and more reliable applicability of the studied models, helping land

146 managers to predict the impact of best management practices based on mulching to runoff and
147 erosion control in olive growing areas.

148

149 **2. MATERIALS AND METHODS**

150

151 **2.1. Study area**

152

153 The experimental site is an olive grove (38.2671° N, 16.1872° E, Locri, Southern Calabria, Italy) at
154 a mean altitude of 114 m a.s.l. (Figure 1a). The olive grove was 10-12 years old at the start of the
155 experiment (2016) and planted with trees of *Olea europea* (cultivar Geracese) at 6 m x 6 m spacing
156 (Figure 1b).




Figure 1 - Location and aerial map (a), and illustrative layout of the experimental equipment (b) to measure the hydrological variables in the experimental site (Locri, Calabria, Italy).

The climate of the area is typically semi-arid Hot-summer Mediterranean (Csa class, according to Koppen classification, Kottek et al., 2006), with mild and rainy winters, and dry and warm summers. The annual average rainfall and minimum/maximum temperatures are 1350 mm and 11 and 28 °C, respectively (historical observations of 1923-2017).

The olive grove has a uniform slope of 20%. The soil is a Eutric cambisol (FAO, 2006) with prevalent clayey texture (28% of sand, 28% of silt and 44% of clay, w w⁻¹). In the olive grove, the

grass cover spontaneously growing over the soil is usually mowed twice a year, in April and August, while the olive trees are pruned each year (in March) and residues are chopped by a shredder (size between 5 and 8 cm). Grass (40%) and pruning residues (60%) are left on the ground surface (around 3 tons ha⁻¹ yr⁻¹ of dry matter) under the tree canopy and in the inter-row areas as mulching cover.

The experimental site in the olive grove consisted of a series of three plots (42-m long and 6-m wide, area of 252 m²) that were hydraulically isolated by metallic sheets, in order to avoid the inflow/outflow of runoff (Figure 1b). The noticeable plot length (which is higher compared to the value suggested by Wischmeier and Smith, 1978, close to 20 m) allows the collection of a fair quantity of runoff also for mid-intensity events as well as the activation of erosion forms (e.g., rill erosion) that in short-length plots (especially with clayey soil texture) rarely or only partly develop. Each plot simulated one of the following soil management practices (SCPs): (i) Standard Protection of soil (hereinafter indicated as SP); (ii) Mechanical Tillage (MT); and (iii) No-Tillage and Retention of pruning residues at dry matter doses of 350 g m⁻² (NTR).

SP, assumed as the control practice, represents the ideal cover layer for soil protection; to simulate this condition, the plot was covered by a horizontal plastic net (mesh of 1 mm²), placed 10 cm over the ground, allowing the growth of living vegetation. The net reduces the splash erosion and intercepts a share of the precipitation, protecting the soil from the direct raindrop impact, but does not cause concentrate flow on the ground surface during heavy storms. The MT, carried out in autumn and spring by a rotary tiller, is the most common SCP in farmers of Southern Italy, who, however, complain about high soil losses in their olive groves. Under the NTR, the soil was covered with pruning and grass residues distributed at a dose of 3.5·10³ kg ha⁻¹ (in spring) every year as mulching. In a previous study (Bombino et al., 2021), this dose was able to modify the hydrological response of soil with significantly lower runoff and erosion rates.



Figure 2 – The plots with the three different SCPs monitored in Locri (Calabria, Italy).

Legend: Soil Management Practices: SP = Standard Protection of soil; MT = Mechanical Tillage; NTR = No Tillage and Retention of vegetal residues.

2.2. Hydrological measurements

A campaign of hydrological measurements was carried out between January 2016 and June 2018, one year after the implementation of the SCPs (January 2015). Sub-hourly (5-minute interval) data of rainfall depth and intensity were measured at the gauging station of Antonimina (327 m a.s.l.), 1-km far from the experimental site and used to calculate rainfall intensity for each event.

Surface runoff after the 26 monitored rainfalls was measured by an ultrasonic flow logger (Stingray 2.0 - Greyline Inc.). For each event, the runoff volume was stored (using a by-pass) into a 1000-litre tank, connected by a v-shaped collector and a pipe at the bottom side of the plots. To avoid manipulating too large volumes of runoff water and sediments (over the capacity of the tanks) when abundant rainfall occurred, we used an automatic hydraulic device, which discarded 90% of the runoff water generated in the plot and collected the remaining 10% of runoff and sediment flows.

This was simply made by a by-pass device with a “t-shaped” pipeline. Measured runoff volumes were upscaled to the original amount generated in the plot as a simple product by ten.

For erosion modelling, fifteen events with intensity higher than 50 mm h⁻¹ calculated on 30-min duration, were selected. This rainfall intensity is typical of erosive events occurring in this area every 30–50 years (Bombino et al., 2019). For sediment yield measurements, the runoff volume inside the tanks was manually shaken and three samples, totalling 0.5 litres, were collected. Each composite sample was dried in oven at 105 °C for 24 hours and the dried sediment was weighted and referred as the sample volume, in order to measure the sediment concentration (Hudson, 1993). The latter was multiplied by the runoff volume to estimate the soil loss and thus the erosion after each precipitation event.

2.3 Model implementation in the experimental plots

A short description of the four models tested in this study is reported in the Appendix 1 of the Supplementary Material. The model implementation procedures in the experimental plots are explained in the following sub-sections.

2.3.1. SCS-CN model

The sub-hourly (5-minute interval) rainfall data measured at the gauging station of the experimental site were aggregated at the daily scale and needed as input to the SCS-CN model. The AMC was derived for each event analysing the antecedent 5-day rainfall depths. The soil hydrological group was assumed according to the Soil Map of Calabria (ARSSA - Regional Agency for Agricultural Services, 2003) and with reference to Bombino et al. (2021), who reported values of the saturated hydraulic conductivity for the same soils and conditions. Due to very small number of measurements available in the experimental design, the calibration of the CN values for olive orchards was not possible. Consequently, the CN values (“default” CN) used as input in the SCS-CN model were derived from the original tables of the USDA Soil Conservation Service (USDA-SCS, 1972) (Table 1).

2.3.2 Horton equation

The infiltration rate (Appendix 1 Eq. 10) was calculated by interpolating the infiltration curves measured using a double-cylinder infiltrometer for each SCPs. The infiltrometer consisted of two coaxial cylinders having inner and outer diameters of 0.32 and 0.57 m, respectively, and height of 0.30 m, and driven into the soil to a depth of 150 mm. For each measurement, updated in a 6-monthly step, the test measured the time needed for the infiltration of 20 mm of water in the cylinders filled with 50-70 mm of clean water. The infiltration test was repeated until three equal time measurements had been recorded between filling operations (Bombino et al., 2021; Zema et al., 2019).

For the 26 events, the hyetograph $i(t)$ was derived and the difference between $i(t)$ and $f(t)$ gave the runoff rate $q(t)$ at a time step of 5 minutes. Given the very short time of concentration (lower than 1 minute) of the plot, the surface runoff stop was considered the same as the rainfall end.

2.3.3 MUSLE equation

The MUSLE model is usually applied at the catchment scale, but there are examples of its use at plot scale (e.g., McConkey, 1997; Pongsay et al., 2010). In the expression of the MUSLE equation (Appendix 1 Eq. 11), Q is the observed runoff after each event, while q_p was the peak flow predicted by Horton method. For the site-specific factors a and b , the values were 0.87 and 0.56 respectively taken from the experiences of Williams (1982). The K-factor was calculated using the nomograph of Wischemeier and Smith (1978). The C-factor, which depends on the management practice applied to the soil, was related to the tree density canopy diameter, and ground cover of the plots. In this study, this USLE C-factor was calculated following the study by Bombino et al (2002), who proposed an empirical equation based on canopy cover and aboveground biomass. Finally, the values of the P-factor were always set to one for all SCPs (Table 1).

2.3.4 USLE-M equation

The runoff coefficient Q_R was calculated as:

$$Q_R = Q/P_e$$

where Q is the measured runoff volume (mm) and P_e the observed rainfall depth (mm). The R_e factor was calculated following the common method proposed by Renard et al. (1991) for the USLE model.

$$R_e = EI_{30}/1735$$

where R_e is the rainfall R-factor ($\text{MJ mm ha}^{-1} \text{ h}^{-1}$), E is the rainfall kinetic energy for each event (tons m ha^{-1}) and I_{30} is the maximum rainfall intensity for a duration of 30 minutes (mm h^{-1}). Different values for C and K were proposed for use with USLE-M by Kinnel and Risse (1998), hereafter indicated as K_{UM} and C_{UM} , while the P factor is the same as the MUSLE model.

2.4 Model calibration

The SCS-CN, MUSLE and USLE-M models were initially run with default parameters. However, due to the unsatisfactory predictions (see section 3), the models were calibrated taking into account the most sensitive input parameters (CN for the SCS-CN model, and the C factor for the MUSLE and USLE-M equations). The C-factor is the most used calibration parameter for USLE-family erosion models (Biddoccu et al., 2020; Hammad et al., 2004; Khemiri and Jebari, 2021). For this reason, the hydrological effects of mulching practice were taken into account by tuning this factor.

The objective of the calibration process was the minimisation of both the coefficient of efficiency (Nash and Sutcliffe, 1970) and the error between the mean values of the observations and simulations of runoff or soil loss manually by the trial-and-error procedure. No calibration was carried out for the Horton equation, because the calibration was made through the infiltration tests during the hydrological measurements. For the used models, the default and calibrated parameters and their sources, are listed in Table 1.

Table 1 - Values of input parameters adopted to simulate surface runoff volumes and soil loss using the SCS, Horton MUSLE and USLE-M models applied in the three SCPs monitored in Locri (Calabria, Italy).

<i>Model</i>	<i>Input parameter</i>	<i>Measuring unit</i>	<i>Soil management practice</i>		
			<i>MT</i>	<i>SP</i>	<i>NTR</i>

			<i>Default model</i>	<i>Calibrated model</i>	<i>Default model</i>	<i>Calibrated model</i>	<i>Default model</i>	<i>Calibrated model</i>
<i>SCS-CN</i>	CN	-	88	85	79	70	90	75
	λ	-	0.2					
<i>Horton</i>	f_o	mm h ⁻¹	22.6		10.2		20.6	
	f_c	mm h ⁻¹	3.6		6.5		4.8	
	k	h ⁻¹	0.05					
<i>MUSLE</i>	a	-	0.87					
	b	-	0.56					
	K-factor	tons h MJ ⁻¹ mm ⁻¹	0.16					
	C-factor	-	0.78	0.4	0.4	0.09	0.09	0.045
	P-factor	-	1					
<i>USLE-M</i>	a	-	0.87					
	b	-	0.56					
	Average R _e -factor	MJ mm ha ⁻¹ h ⁻¹	67.5					
	K _{UM} - factor	tons h MJ ⁻¹ mm ⁻¹	0.02					
	C _{UM} - factor	-	0.08	0.06	0.04	0.02	0.02	0.01
	P-factor		1					

Notes: Soil Management Practices: SP = Standard Protection of soil; MT = Mechanical Tillage; NTR = No Tillage and Retention of vegetal residues of 350 g m⁻². CN = Curve number; λ = initial abstraction ratio; f_o = maximum infiltration rate; f_c = minimum infiltration rate; k = decay rate of infiltration in time; a and b = site-specific factors; R_e = RUSLE rainfall R-factor; K , C and P = factors of the MUSLE model; K_{UM} and C_{UM} = factors of the USLE-M model.

2.5 Model performance evaluation

Two separate approaches were adopted for model performance evaluation. A qualitative procedure consisted of visually comparing observed and simulated values in scatterplots. A quantitative evaluation was also adopted using statistics (i.e. maximum, minimum, mean and standard deviation

of both observed and simulated values) and a set of indexes, commonly used in hydrological modelling (Table 2).

Table 2 – Indexes used to evaluate the prediction capacity of the SCS-CN and Horton models applied to plots subjected to the three SCPs (Locri, Southern Italy).

Index	Equation	Acceptance limits or optimal values
	r^2	$r^2 > 0.50$ (Santhi et al., 2001; Van Liew & Garbrecht, 2003; Vieira et al., 2018)
	NSE	Model accuracy (Van Liew et al., 2003): - good if $NSE \geq 0.75$ - satisfactory if $0.36 \leq NSE < 0.75$ - unsatisfactory if $NSE < 0.36$
	CP	< 0.25 (Moriassi et al., 2007) - $PBIAS < 0$ indicates model underestimation - $PBIAS > 0$

		indicates model overestimation (Gupta et al., 1999)
--	--	---

Notes: n = number of observations; O_i , P_i = observed and predicted values at the time step i ; $\bar{O}$ = mean of observed values; SD = standard deviation.

3. Results and discussion

3.1. Hydrological characterisation

Throughout the 2.5-year observation period, the annual rainfall recorded at the Antonimina meteorological station was between 815 and 1275 mm yr⁻¹, and the maximum daily precipitation was 183 mm. Twenty-six rainfalls were recorded with depths between 16.6 mm (25 March 2018) and 183 mm (25 November 2016) (Figure 3). All these rainfalls were classified as erosive events (that is, with depth over 13 mm), according to Wischmeier and Smith (1978).

These 26 rainfall events generated runoff volumes from 7.4 mm to 146 mm, and these extreme values were recorded under the MT treatment. In the plots subject to the other treatments, the runoff measured was in the range 9.3 – 137.3 mm (SP) and 9.1 – 109.8 mm (NTR) (Figure 3). The runoff produced in the NTR treatment was not significantly different from the corresponding values of the control SP, but significantly lower than MT plots (Figure 3). During a rainfall event, we noticed that the net installed in the SP plots fragmented the raindrops, which passed through the net, reducing the kinetic energy of rainfall on soil and thus the splash erosion.





Figure 3 - Surface runoff volume measured after natural rainfalls in the experimental plots subjected to three soil management practices (Locri, Southern Italy).

Legend: Soil Management Practices: SP = Standard Protection of soil; MT = Mechanical Tillage; NTR = No Tillage and Retention of vegetal residues.

The event runoff coefficients were in the range 30% – 82% for MT, 25.9% – 79.6% for SP, and 25.8% – 69.8% for NTR. The runoff coefficient in the latter SCPs was significantly different from MT and SP. The sediment yield generated by the sample of 15 events ranged from 0.001 to 0.19 tons ha⁻¹ (MT), 0.01 – 0.12 (SP), and 0.01 – 0.05 (NTR) tons ha⁻¹ (Figure 4). On average, the sediment yielded in the NTR treatment was not significantly different from the corresponding values of the control SP, but significantly lower than MT.



364

365 Figure 4 - Soil loss measured after natural rainfalls in the experimental plots subjected to three soil
366 management practices (Locri, Southern Italy).

367 *Legend: Soil Management Practices: SP = Standard Protection of soil; MT = Mechanical Tillage;*
368 *NTR = No Tillage and Retention of vegetal residues.*

369

370 3.2. Runoff modelling

371

372 Both the evaluated models (SCS-CN and Horton) showed acceptable coefficients of determination
373 ($r^2 > 0.53$), which show strong correlations between observations and predictions of runoff volumes
374 (Figure 5a, b, c and Table 3). The prediction accuracy of the Horton model in simulating runoff
375 volume was generally low. Moreover, although the model efficiency was satisfactory for three of
376 the three simulated SCPs ($NSE > 0.54$), the value of NSE was poor for the NTR practice and the
377 differences between the mean observed and predicted runoff volumes were always over 30%.

378

379 Model inaccuracy is attributed to the noticeable overestimation of the modelled runoff volumes,
380 shown by the negative values of PBIAS (i.e., over 0.30) (Table 3), since the model was not
381 calibrated and the infiltration rate curves, although updated every six months, were not able to

reproduce the variability of infiltration rates over time. Also, the variability of the infiltration rate between the areas beneath the tree canopies and the lanes, which is typical of an orchard, may explain the outlined model inaccuracy to simulate runoff. In this study, infiltration was measured in the lanes to reduce interferences with trees, and this could have affected the model reliability.

Runoff predictions using the SCS-CN model running with default parameters were not satisfactory. The runoff volumes were slightly over-predicted by the SCS-CN model ($PBIAS < 0$) for NTR, and under-predicted for MT and SP plots ($PBIAS$ equal to 0.09 and 0.34, respectively). The model prediction accuracy was poor for SP ($E = 0.49$) and satisfactory for MT, and NTR plots (E equal to 0.71 and 0.65, respectively), but not optimal (in this case E would be over 0.75).

To improve the model reliability, the CNs were decreased in all plots during the calibration, which noticeably improved the runoff prediction capability of the SCS-CN model. The model's tendency to over- or under-prediction decreased, particularly for the SP plot ($PBIAS$ from 0.34, before calibration, to 0.13, with calibrated CN). Calibration generally gave runoff prediction close to the corresponding observations for all the investigated SCPs. The differences between the observed and simulated mean runoff were lower than 7% with a minimum of 3.4% recorded for MT plot (Figures 5a and Table 3). The optimal values of model efficiency were good ($NSE > 0.85$). Further model simulations using higher CNs in winter and lower values in summer did not improve the runoff prediction accuracy (data not shown). The use of mulching leads to further decrease the hydrological response of soils.

The calibrated CNs, although being lower compared to the default values, were higher compared to the values suggested for olive groves with clay soils (between 64 and 88) by Romero et al. (2007). However, these authors carried out their modelling experience in olive groves with a slope of 5%, which is much lower compared to our experimental plots (Table 1). Only the CN values calibrated for mulching were close to the experimental values by Romero et al. (2007), who, however, did not evaluate the hydrological effects of mulching.

Other modelling experiences using the SCS-CN model, Taguas et al. (2015a) successfully used a CN close to 66 to model runoff in the CN-based DWBR (Daily Water Balance and Runoff) model in a large olive grove of Southern Spain. The same authors achieved optimal CNs between 83 and 87 in a small catchment in the same environment (Taguas et al., 2015a). In clayey olive groves of

Southern Italy, the AnnAGNPS model was able to predict with accuracy runoff volumes, after calibration of the CN-based rainfall-runoff sub-component (Bisantino et al., 2013). Good model performances were also shown by Uwizeyimana et al. (2019) and Jain et al. (2006) in applications of the SCS-CN model in clayey soils of Rwanda and USA, respectively.

This study suggests the feasibility of using the SCS-CN method in similar conditions as the experimental soils and slopes of Southern Italy. However, the model should be further validated in the same climate using further experimental data on rainfall-runoff relationships in olive groves with different soils and slopes. Moreover, we feel the need to (i) investigate the performance of the suggested CN values at the catchment scale, (ii) implement the effect of various soil moisture accounting systems, and (iii) extend the suggested CNs to a broader range of regions, in accordance with Soulis (2021).


Improvements in the available conversion equations for AMCs, which were prepared in non-arid environments (Farran & Elfeki, 2020), may be beneficial to refine runoff estimations using the SCS-CN method. Finally, since the SCS-CN method does not reproduce the changes in soil properties due to management or other factors, more studies may improve the model simulation of temporal evolution of soil properties (Romero et al., 2007). Until then, our results indicate that the suggested values of CN should be used instead of the standard SCS values for runoff predictions in olive groves of the Mediterranean region with similar soils, climate, and management conditions.

Table 3 - Values of the indicators evaluating runoff predictions capacity of the SCS-CN and Horton models applied to plots subjected to the three SCPs (Locri, Southern Italy).


<i>Soil condition</i>	<i>Variable</i>	<i>Model</i>	<i>Input CN</i>	<i>Mean [mm]</i>	<i>Standard deviation [mm]</i>	<i>r²</i>	<i>NSE</i>	<i>PBIAS</i>
MT	Observed			28.85	31.73	-	-	-
	Simulated	Horton		37.41	34.68	0.73	0.65	-0.30
		SCS-CN	Default	26.12	25.08	0.72	0.71	0.09
			Calibrated	29.87	34.88	0.93	0.91	-0.04
SP	Observed			26.52	30.07	-	-	-
	Simulated	Horton		34.68	30.09	0.65	0.54	-0.31
		SCS-CN	Default	17.47	13.83	0.74	0.49	0.34
			Calibrated	23.02	25.62	0.97	0.94	0.13

NTR	Observed			22.06	23.89	-	-	-
	Simulated	Horton		28.62	29.22	0.53	0.26	-0.30
		SCS-CN	Default	25.70	23.44	0.67	0.65	-0.16
			Calibrated	25.27	29.16	0.93	0.85	-0.16


439 Notes: Soil Management Practices: SP = Standard Protection of soil; MT = Mechanical Tillage; NTR = No Tillage and
440 Retention of vegetal residues; r^2 = coefficient of determination; NSE = Nash & Sutcliffe, coefficient of efficiency;
441 PBIAS = percent bias.



(a)



(b)



(c)

Figure 5 - Scatterplots of observed vs. simulated runoff volumes using the SCS-CN (with default or calibrated CNs) and Horton models in the plots simulating three SCPs (a, MT; b, SP, and c, NTR) (Locri, Southern Italy).

Legend: Soil Management Practices: SP = Standard Protection of soil; MT = Mechanical Tillage; NTR = No Tillage and Retention of vegetal residues.

3.3. Erosion modeling

Erosion models with default C-factors showed a poor prediction capacity for soil losses measured under all the three SCPs. The coefficient of determination was over the acceptance limit of 0.50 only for the MT plot (Figure 6a); both the coefficients of efficiency and the differences between the mean observed and simulated soil losses were poor ($NSE < 0$ and errors over 17% with a peak of +70%). This inaccuracy is mainly attributed to the over-estimation (in all the modelled SCPs for the MUSLE and USLE-M models) tendency of the observed soil losses, as clearly shown by the large values of the PBIAS index (always under 0.16 with a peak of -2.42 recorded for the MUSLE model) (Table 4 and Figure 6).

The over-prediction of the MUSLE model was reported in some other studies carried out for different environments (Noor et al., 2010; Shen et al., 2009; Chen and Mackay, 2004). The low

prediction capability was attributed to the fact that the model is applied in an environmental context that is different from those for which the MUSLE model was developed. More generally, Nearing (2000) and Flanagan & Nearing (1995) have highlighted that small soil loss is usually over-predicted by USLE family models.

The observed over-estimation tendencies shown by both erosion models suggests their calibration through the C-factor for each SCP. Therefore, this factor was decreased for all SCPs in order to reduce these tendencies (Table 1). For both the MUSLE and USLE-M models, the calibration process was considered necessary for improving their prediction accuracy. For instance, Di Stefano et al. (2007) and Bagarello et al. (2015), applying the USLE-M in plots of Western Sicily (Italy), highlighted the importance of the calibration process to make possible its adaption to the different climatic and edaphic conditions.

In this study, calibration noticeably increased the prediction accuracy of both models. The coefficients of determination (Figures 6 a, b, c and Table 4) were over 0.75, with a maximum of 0.92 (USLE-M model applied to SP plot). For almost all the SCPs evaluated, the coefficients of efficiency were good ($NSE > 0.75$) (Table 4). Thanks to the calibration process, the tendency to erosion over-estimations was noticeably reduced, both the calibrated models showing values of the PBIAS indexes under 0.09 (noticeably lower compared to the acceptance limit of 0.55, suggested by Moriasi et al., 2007, for erosion modelling).

The calibrated models produced differences between the mean observed and predicted soil losses lower than 10% (MUSLE model applied to SP plots) and 8% (USLE-M model predicting soil loss under NTR management). Even a simple visual comparison of the observed vs. modelled soil losses shows a low scattering of points around the line of perfect agreement (Figure 6).

The satisfactory performance of the MUSLE model was somewhat surprising given that this model has been applied at the pilot scale in only a few previous studies after calibration (McConkey et al., 1997; Pongsay et al., 2010). In order to further improve the MUSLE performance in erosion modelling, Sadeghi et al. (2014) and Michalec et al. (2017) proposed its calibration using a long-lasting series of observations, which allows the reduction of model uncertainty, even if a good correlation has been reported after a few erosive events. Moreover, Gwapedza, et al. (2018)

suggested testing sensitivity to different physical factors including plot or basin size by adopting a distributed form of the plot in order to improve the model performance.

The underprediction detected for these USLE-M and MUSLE models in this study is in contrast with the usual behaviour of USLE-family models, which generally overpredict the lower soil loss (Nearing, 2000). Other modelling experiences highlighted that the applications of USLE-family models in different contexts can both over- or under-predict soil loss. More specifically, Biddoccu et al. (2020), applying the RUSLE model to the soils with permanent cover crops, predicted soil losses that were lower or close to soil formation rate in Europe. Bagarello et al. (2017; 2020), using the USLE-M model, reported an underestimation of soil loss for lower-intensity events.

Since five (K, L, S, C and P) of the six USLE-factors are common in the two models under each SCP, it is possible to compare the effects of the R-factor (linked to the rainfall erosivity) on the predicted soil losses. It cannot be excluded that the higher accuracy found for the USLE-M in simulating erosion of soils treated with mulching (NTR) is due to the information provided through the use of observed Q and q_p in the R-factor, missing in the MUSLE model. The applications of Q and q_p simulated in modelling soil loss in the absence of measured input variables could reduce this accuracy. Soil mulching reduces erosion limiting the particle detachment due to the rainsplash process rather than limiting sediment transport due to overland flow (Singer et al., 1981; Pan et al., 2010; Li & Xie, 2014). Conversely, the best performance of the MUSLE model detected in the MT and SP plots may be linked to the presence of a factor linked to the peak flow rate, which is better able to reproduce the particle detachment due to the erosivity of the overland (laminar and concentrated) flow. However, the practical applicability of the MUSLE model is lower, since the determination of the q_p sub-factor is generally less easy compared to the coefficient of runoff, only required by the USLE-M equation.

In our study, further attempts to improve the erosion prediction capacity of both models using other calibration strategies were not successful. For instance, neither the use of the C-factors suggested by the European Soil Data Center (ESDC) (Panagos et al., 2015) or the input of seasonally-varying values (that is, higher and lower values in winter and summer, respectively, Sadeghi et al., 2014), did not improve the prediction performance of both models (data not shown).

In other studies, model accuracy and reliability under variable C-factors were evaluated in different environmental conditions (Risse et al., 1993; Laflen et al., 2004). At the European scale, Panagos et al. (2015) proposed C-factors between 0.1 and 0.3 (Italy), and 0.22 and 0.24 (Spain) were suggested for croplands of those countries. Several authors proposed C-values for cultivation operations in olive groves (Moreira Madueño, 1991, 0.4; Kok et al. 1995, 0.54; Giraldez et al. 1989, 0.4 for conventional tillage and 0.45 for no tillage; Gomez et al., 2003, 0.41 for conventional and no tillage). Gomez et al. (2021) found a range between 0.12 and 0.50 for the different soil management declared by farmers in Southern Spain, while Brini et al. (2021) and Chafai et al. (2020) proposed for olive groves generic values of 0.2 and 0.5, respectively. Folly et al. (1996) used much higher C-values (0.7) for olive areas, and Lopez-Vicente and Navas (2009) even suggested a mean C-factor of one for olive trees in a catchment of Spanish pre-Pyrenees.


Modelers frequently propose C-factors based on poor understanding of the methodological and geographical origin of these values and often without a description of the specific crop management systems. Therefore, the results may not be compatible with other sites (Rocha and Sparovek, 2021). Therefore, the estimation of the site-specific C-factors using locally measured data, as was the aim of our study, increases the erosion prediction accuracy of USLE-family models (Kebede et al., 2021).

In this investigation, the C-values proposed for the modelled SCPs were calibrated using observations collected at only one site following a standard procedure that is based on approximations and visual comparison. In many cases, this procedure can be misleading and must be validated in other environmental conditions or supported by external parameters. For example, Soil Moisture Tension (SMT) comparison is one suitable method to detect the difference between the measured C-factor and the RUSLE C-factor with SMT (Hammad et al., 2004). Bearing in mind the limitation of our study, the C-value proposed for mulched plots could be reliable at least for steep and clayey soils of Mediterranean conditions and fills the lack of similar values for mulching applications in the literature.

Further improvements of the USLE-family models could consider: (i) the use of a subfactor, which introduce the modification of the erosion risk due to changes in the soil moisture content, according to the suggestions by Biddoccu et al. (2020); and (ii) the evaluation of the effects of management on

565 soil conditions, to improve the understanding of the system and to predict its temporal changes
566 (Gomez et al., 2003).

567




(a)

568


569

570



571

(b)



(c)

Figure 6 - Scatterplots of observed vs. simulated soil losses using the MUSLE and USLE-M models (with default or calibrated C factor) in the plots simulating three SCPs (a, MT; b, SP, and c, NTR) (Locri, Southern Italy).

Legend: Soil Management Practices: SP = Standard Protection of soil; MT = Mechanical Tillage; NTR = No Tillage and Retention of vegetal residues.

Table 4 - Values of the indicators evaluating runoff predictions capacity of the MUSLE and USLE-M models applied to plots subjected to the three SCPs (Locri, Southern Italy).

Soil condition	Variable	Model	C-factor	Mean [tons ha ⁻¹]	Standard deviation [tons ha ⁻¹]	r ²	NSE	PBIAS
MT	Observed			0.09	0.05	-	-	-
	Simulated	MUSLE	Default	0.12	0.12	0.60	-3.50	-0.32
			Calibrated	0.09	0.06	0.87	0.76	-0.02
		USLE-M	Default	0.11	0.07	0.66	-0.23	-0.22
			Calibrated	0.09	0.05	0.89	0.87	0.02
SP	Observed			0.03	0.04	-	-	-
	Simulated	MUSLE	Default	0.12	0.05	0.38	-6.67	-2.42
			Calibrated	0.04	0.03	0.83	0.81	-0.11
		USLE-M	Default	0.05	0.04	0.33	-0.18	-0.49
			Calibrated	0.03	0.04	0.92	0.90	0.05
NTR	Observed			0.02	0.01	-	-	-
	Simulated	MUSLE	Default	0.02	0.02	0.49	-2.38	-0.16
			Calibrated	0.02	0.01	0.78	0.76	-0.03
		USLE-M	Default	0.02	0.02	0.14	-2.57	-0.23
			Calibrated	0.02	0.01	0.86	0.83	0.07

Notes: Soil Management Practices: SP = Standard Protection of soil; MT = Mechanical Tillage; NTR = No Tillage and Retention of vegetal residues; r² = coefficient of determination; NSE = Nash & Sutcliffe, coefficient of efficiency; PBIAS = percent bias.

4. Conclusions

This study has modelled runoff and erosion for an olive grove with a steep slope and clayey soil under different SCPs typical of Southern Italy, providing important information regarding four research questions. Firstly, the dominant runoff generation mechanism of the experimental soils may be due to soil saturation (as shown by the higher runoff prediction accuracy of the SCS-CN model compared to the infiltration model proposed by Horton) rather than to infiltration excess, as it would be expected in soils of the semi-arid environments. Secondly, soil loss was mainly due to rainsplash erosion in the soils treated with mulching (suggested by the better performance for this management by the USLE-M model, whose rainfall erosivity is based on the R-factor performed better). Soil loss produced under the other modelled SCPs (mechanical tillage and total soil protection) mainly depends on overland flow, which determines particle detachment (suggested by the higher accuracy of the MUSLE equation, which includes parameters related to surface runoff). Thirdly, for all soil conditions, the SCS-CN model provides more accurate predictions of surface runoff as compared to the Horton equation. For soil erosion, the MUSLE model showed better performances in soils subject to mechanical tillage or total protection, while the USLE-M equations provided more accurate soil loss predictions in plots treated with mulching. Fourthly, our study confirms other literature results, stating that the calibration process is a prerequisite for the tested models for accurate predictions of surface runoff and soil loss. For olive orchards with a steep slope and clayey soil of Southern Italy the following two sets of CNs and C-factors values can be suggested for applications of the SCS-CN and USLE-family models, respectively:

- 95 (MT), 70 (SP), and 85 (NTR) for runoff modelling;
- 0.4 (MT), 0.2 (SP), and 0.1 (NTR) for soil loss predictions.

Overall, this study has confirmed the viability of the SCS-CN and USLE-family models to simulate runoff and water erosion in olive groves of the Mediterranean semi-arid environments under different soil conditions. Although this assumption is limited to the experimental conditions, the results are encouraging for further application of these conceptually simple and widely-used models in analogous climatic and geomorphologic conditions. Further modeling studies should also enlarge the spatial scale from plots to watersheds, using more complex hydrological models including the studied equation as rainfall-runoff

transformation and erosive components. Once validated in a wider range of environmental contexts, these models may support the land managers to control runoff and erosion in agricultural soils that are prone to hydrogeological risks.

Funding

This work was funded by the Italian Minister of Education and Research in the framework of the project PON“ Modelli Sostenibili e Nuove Tecnologie per la Valorizzazione delle Olive e dell’Olio Extravergine di Oliva Prodotto in Calabria”. Grant ID.: PON03 PE00090_2. This work was also supported by the project PID2019-105793RB-I00 (Spanish Government).

References

Arnold, J.G., Srinivasan, R., Muttiah, R.S., & Williams, J.R., (1998). Large area hydrologic modeling and assessment part I: model development 1. *Journal of the American Water Resources Association*, 34(1), 73-89. <https://doi.org/10.1111/j.1752-1688.1998.tb05961.x>

ARSSA Calabria (Regional Agency for Development and Services in Agriculture), (2003). Pedological map scale 1:250.000. Agenzia Regionale per lo Sviluppo ed i Servizi in Agricoltura della Calabria. Catanzaro (Italy) (in Italian).

Bagarello, V., Ferro, V., & Pampalone, V., (2015). A new version of the USLE - MM for predicting bare plot soil loss at the Sparacia (South Italy) experimental site. *Hydrological Processes*, 29(19), 4210-4219. <https://doi.org/10.1002/hyp.10486>

Bagarello, V., Ferro, V., & Pampalone, V., (2017). Comparing two applicative criteria of the soil erosion physical model concept. *Vadose Zone Journal*, 16(12), 1-10.) <https://doi.org/10.2136/vzj2017.06.0117>

Bagarello, V., Ferro, V., & Pampalone, V., (2020). A comprehensive analysis of Universal Soil Loss Equation - based models at the Sparacia experimental area. *Hydrological Processes*, 34(7), 1545-1557. <https://doi.org/10.1002/hyp.13681>

- Beaufoy, G., (2002). The environmental impact of the olive oil production in the European Union: practical options for improving the environmental impact. Available on: <http://www.ec.europa.eu/environment/agriculture/pdf/oliveoil.pdf> (accessed 11.03.2019).
- Bezak, N., Mikoš, M., Borrelli, P., Alewell, C., Alvarez, P., Anache, J. A. A., ... & Panagos, P. (2021). Soil erosion modelling: A bibliometric analysis. *Environmental research*, 197, 111087.
- Biddoccu, M., Guzmán, G., Capello, G., Thielke, T., Strauss, P., Winter, S., ... & Gómez, J.A. (2020). Evaluation of soil erosion risk and identification of soil cover and management factor (C) for RUSLE in European vineyards with different soil management. *International Soil and Water Conservation Research*, 8(4), 337-353. <https://doi.org/10.1016/j.iswcr.2020.07.003>
- Bingner, R.L., & Theurer, F.D., (2001). AnnAGNPS: Estimating sediment yield by particle size for sheet and rill erosion. In 7th Federal Interagency Sedimentation Conference: Sedimentation Monitoring, Modeling, and Managing, 1: I-1 to I-7, Washington, DC: Interagency Advisory Committee on Water Data, Subcommittee on Sedimentation.
- Bisantino, T., Bingner, R., Chouaib, W., Gentile, F., & Trisorio Liuzzi, G., (2015). Estimation of runoff, peak discharge and sediment load at the event scale in a medium size Mediterranean watershed using the AnnAGNPS model. *Land degradation & development*, 26(4), 340-355. <https://doi.org/10.1002/ldr.2213>
- Bombino, G., Porto, P., & Zimbone, S.M., (2002). Evaluating the crop and management factor C for applying RUSLE at plot scale. In 2002 ASAE Annual Meeting (p. 1). American Society of Agricultural and Biological Engineers.
- Bombino, G., Denisi, P., Gómez, J.A., Zema, D.A., (2019). Water infiltration and surface runoff in steep clayey soils of olive groves under different management practices. *Water*, 11(2), 240. <https://doi.org/10.3390/w11020240>
- Bombino, G., Denisi, P., Gomez J.A., Zema, D. A., (2021). Mulching as best management practice to reduce surface runoff and erosion in steep clayey olive groves, *International Soil and Water Conservation Research*, <https://doi.org/10.1016/j.iswcr.2020.10.002>

- Borrelli, P., Alewell, C., Alvarez, P., Anache, J. A. A., Baartman, J., Ballabio, C., ... & Panagos, P. (2021). Soil erosion modelling: A global review and statistical analysis. *Science of the total environment*, 146494.
- Boughton, W., (2005). Catchment water balance modelling in Australia 1960–2004. *Agricultural Water Management*, 71(2), 91-116. <https://doi.org/10.1016/j.agwat.2004.10.012>
- Brini, I., Alexakis, D. D., & Kalaitzidis, C., (2021). Linking Soil Erosion Modeling to Landscape Patterns and Geomorphometry: An Application in Crete, Greece. *Applied Sciences*, 11(12), 5684.
- Burguet, M., Taguas, E. V., & Gómez, J. A. (2017). Exploring calibration strategies of the SEDD model in two olive orchard catchments. *Geomorphology*, 290, 17-28.
- Chafai, A., Brahim, N., & Shimi, N. S., (2020). Mapping of water erosion by GIS/RUSLE approach: watershed Ayda river—Tunisia study. *Arabian Journal of Geosciences*, 13(16), 1-14.
- Chen, E. & Mackay, D.S., (2004). Effects of distribution-based parameter aggregation on a spatially distributed agricultural nonpoint source pollution model. *Journal of Hydrology*, 295, 211–224.) <https://doi.org/10.1016/j.jhydrol.2004.03.029>
- Costantini, E. A., & Dazzi, C. (Eds.). (2013). The soils of Italy. Springer Science & Business Media.
- Covelli, C., Cimorelli, L., Pagliuca, D.N., Molino, B., & Pianese, D., (2020). Assessment of erosion in river basins: A distributed model to estimate the sediment production over watersheds by a 3-dimensional LS factor in RUSLE model. *Hydrology*, 7(1), 13.
- Dabney, S.M., Yoder, D.C., Yoder, & Vieira, D.A.N., (2012). The application of the Revised Universal Soil Loss Equation, Version 2, to evaluate the impacts of alternative climate change scenarios on runoff and sediment yield. *Journal of Soil and Water Conservation*, 67, 343e353. <https://doi.org/10.2489/jswc.67.5.343>
- Di Stefano, C., Ferro, V., Burguet, M., & Taguas, E.V., (2016). Testing the long term applicability of USLE-M equation at a olive orchard microcatchment in Spain. *Catena*, 147, 71-79. <https://doi.org/10.1016/j.catena.2016.07.001>

734

735 FAO. (2006). *Guidelines for soil description*. Rome: Food and Agriculture Organisation of the
736 United States.

737

738 Farran, M. M., & Elfeki, A. M., (2020). Evaluation and validity of the antecedent moisture
739 condition (AMC) of Natural Resources Conservation Service-Curve Number (NRCS-CN)
740 procedure in undeveloped arid basins. *Arabian Journal of Geosciences*, 13(6), 1-17.

741

742 Ferro V., Porto P., (2000) Sediment Delivery Distributed (SEDD) Model, *Journal of hydrologic*
743 *engineering*", n. 5, , pp. 411-422,

744

745 Ferrara, A.; Salvati, L.; Sabbi, A.& Colantoni, A. (2014) Urbanization, Soil Quality and Rural
746 Areas: Towards a Spatial Mismatch? *Science of Total Environment.*, 478, 116–122

747

748 Fisher, J., Scholes, R., & Montanarella, L. (2018). Assessment Report on land degradation and
749 restoration of the Intergovernmental Science-Policy Platform on Biodiversity and Ecosystem
750 Services.

751 Flanagan, D.C. & Nearing, M.A., (1995). USDA Water Erosion Prediction Project: Hillslope
752 Profile and Watershed Model Documentation. NSERL Report No. 10, USDA-ARS National Soil
753 Erosion Research Laboratory, West Lafayette, IN 47907-1194.

754

755 Folly, A., Bronsveld, M. C. and Clavaux, M., (1996). A knowledge-based approach for C-factor
756 mapping in Spain using Landsat TM and GIS. *International Journal of Remote Sensing*, 12, 2401-
757 2415

758

759 Fortugno, D., Boix-Fayos, C., Bombino, G., Denisi, P., Quiñonero Rubio, J. M., Tamburino, V., &
760 Zema, D.A., (2017). Adjustments in channel morphology due to land-use changes and check dam
761 installation in mountain torrents of Calabria (southern Italy). *Earth Surface Processes and*
762 *Landforms*, 42 (14), 2469-2483. <https://doi.org/10.1002/esp.4197>

763

764 Giraldez, J.V., Laguna, A & Gonzalez, P., (1989). Soil conservation under minimum tillage
765 techniques in Mediterranean dry farming. *Soil Technology Series* 1, 139-147.

766

767 Gomez, J.A., Battany, M., Renschler C.S., & Fereres, E., (2003). Evaluating the impact of soil
768 management on soil loss in olive orchards. *Soil Use and Management* 19, 127-134.
769 <https://doi.org/10.1111/j.1475-2743.2003.tb00292.x>.
770

771 Gómez, J.A., Llewellyn, C., Basch, G., Sutton, P.B., Dyson, J. S., & Jones, C.A., (2011). The
772 effects of cover crops and conventional tillage on soil and runoff loss in vineyards and olive groves
773 in several Mediterranean countries. *Soil Use and Management*, 27(4), 502-514.
774

775 Gómez, J.A., Infante-Amate, J, González de Molina, M., Vanwalleghe, T., Taguas, E.V. &
776 Lorite I., (2014a). Olive cultivation, its impact on soil erosion and its progression into yield
777 impacts in Southern Spain in the past as a key to a future of increasing climate uncertainty.
778 *Agriculture*, 4, 170-198. <https://doi.org/10.3390/agriculture4020170>
779

780 Gomez, J.A., (2017). Sustainability using cover crops in Mediterranean tree crops, olives and vines
781 – Challenges and current knowledge. *Hungarian Geographical Bulletin* 66 (1) 13–28. 13.
782 <https://10.15201/hungeobull.66.1.2>

783 Gómez, J. A., Campos, M., Guzmán, G., Castillo-Llanque, F., Vanwalleghe, T., Lora, Á., &
784 Giraldez, J. V. (2018). Soil erosion control, plant diversity, and arthropod communities under
785 heterogeneous cover crops in an olive orchard. *Environmental Science and Pollution Research*,
786 25(2), 977-989.

787 Gómez, J.A., Montero, A.S., Guzmán, G., & Soriano, M.A., (2021). In-depth analysis of soil
788 management and farmers' perceptions of related risks in two olive grove areas in southern Spain.
789 In press *International Soil and Water Conservation Research*.
790 <https://doi.org/10.1016/j.iswcr.2021.01.003>
791

792 Gupta, H.V., Sorooshian, S., & Yapo, P.O., (1999). Status of automatic calibration for hydrologic
793 models: Comparison with multilevel expert calibration. *Journal of Hydrologic Engineering*, 4(2),
794 135-143.
795

796 Gwapedza, D., Hughes, D.A., & Slaughter, A.R., (2018). Spatial scale dependency issues in the
797 application of the Modified Universal Soil Loss Equation (MUSLE). *Hydrological Sciences*
798 *Journal*, 63(13-14), 1890-1900. <https://doi.org/10.1080/02626667.2018.1546388>
799

800 Hammad, A.A., Lundekvam, H., & Børresen, T., (2004). Adaptation of RUSLE in the Eastern Part
801 of the Mediterranean Region. *Environmental Management*, 34(6), 829-841.).
802 <https://doi.org/10.1007/s00267-003-0296-7>
803

804 Hawkins, R.H., (1982). Distribution of loss rates implicit in the SCS-CN runoff equation. Arizona-
805 Nevada Academy of Science.
806

807 Hjelmfelt, A.T., (1991). Investigation of curve number procedure. *Journal of Hydraulic*
808 *Engineering*. 117:725–737.
809

810 Hudson, N.W., (1993). Field Measurement of Soil Erosion and Runoff. FAO Soils Bulletin 68.
811 Rome.
812

813 Jackson W.L., Gebhard K. & van Haveren B.P., (1986). Use of the Modified Universal Soil Loss
814 Equation for average annual sediment yield estimates on small rangeland drainage basins.
815 Published in Drainage Basin Sediment Delivery, IAHS Publ. 159, 413-422
816

817 Jain, M.K., Mishra, S.K., & Singh, V.P., (2006). Evaluation of AMC-dependent SCS-CN-based
818 models using watershed characteristics. *Water Resources Management*, 20(4), 531-552
819 <https://doi.org/10.1007/s11269-006-3086-1>
820

820 Kassam, A., Friedrich, T., Shaxson, F., & Pretty, J. (2009). The spread of conservation agriculture:
821 justification, sustainability and uptake. *International journal of agricultural sustainability*, 7(4),
822 292-320.
823

823 Kebede, B., Tsunekawa, A., Haregeweyn, N., Adgo, E., Ebabu, K., Meshesha, D.T., ... & Fenta, A.
824 A., (2021). Determining C-and P-factors of RUSLE for different land uses and management
825 practices across agro-ecologies: case studies from the Upper Blue Nile basin, Ethiopia. *Physical*
826 *Geography*, 42(2), 160-182. Doi: 10.1080/02723646.2020.1762831
827

828 Khemiri, K., & Jebari, S., (2021). Évaluation de l'érosion hydrique dans des bassins versants de la
829 zone semi-aride tunisienne avec les modèles RUSLE et MUSLE couplés à un Système
830 d'information géographique. *Cahiers Agricultures*, 30, 7. doi: 10.1051/cagri/2020048
831

832 Kinnell, P.I.A., & Risse, L.M., (1998). USLE-M: Empirical modeling rainfall erosion through
833 runoff and sediment concentration. *Soil Science Society of America Journal*, 62(6), 1667-1672.

834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866

Kottek, M., Grieser, J., Beck, C., Rudolf, B., & Rubel, F., (2006). World map of the Köppen-Geiger climate classification updated. *Meteorologische Zeitschrift*, 15(3), 259-263.

Kok, K., Clavaux, M.W., Heerebout, W.M., & Bronsveld, K., (1995). Land degradation and land cover change detection using low-resolution satellite images and the CORINE database: a case study in Spain. *ITC journal*, 217-228.

Laflen, J.M., Flanagan, D.C., & Engel, B.A., (2004). Soil erosion and sediment yield prediction accuracy using WEPP. *Journal of the American Water Resources Association*, 40(2), 289-297. <https://doi.org/10.1111/j.1752-1688.2004.tb01029.x>

Li, X., Niu, J., & Xie, B., (2014). The effect of leaf litter cover on surface runoff and soil erosion in Northern China. *PloS one*, 9(9), e107789. <https://doi.org/10.1371/journal.pone.0107789.t004>

Lian, H., Yen, H., Huang, J.C., Feng, Q., Qin, L., Bashir, M.A., ... & Liu, H., (2020). CN-China: Revised runoff curve number by using rainfall-runoff events data in China. *Water research*, 177, 115767. <https://doi.org/10.1016/j.watres.2020.115767>

López-Vicente, M., & Navas, A., (2009). Predicting soil erosion with RUSLE in Mediterranean agricultural systems at catchment scale. *Soil science*, 174(5), 272-282. <https://doi.org/10.1097/SS.0b013e3181a4bf50>

Massetti, L., Grassi, C., Orlandini, S., & Napoli, M. (2020). Modelling hydrological processes in agricultural areas with complex topography. *Agronomy*, 10(5), 750.

McConkey, B.G., Nicholaichuk, W., Steppuhn, H., & Reimer, C. D., (1997). Sediment yield and seasonal soil erodibility for semiarid cropland in western Canada. *Canadian Journal of Soil Science*, 77(1), 33-40. <https://doi.org/10.4141/S95-060>

Michalec, B., Wałęga, A., Cupak, A., & Strutyński, M., (2017). Verification of the MUSLE to determine the amount of suspended sediment. *Carpathian Journal of Earth and Environmental Sciences*, 12(1), 235-244.

867 Mishra, S.K., & Singh, V.P., (1999). Another look at SCS-CN method. *Journal of Hydrologic*
868 *Engineering*, 4(3), 257-264. [https://doi.org/10.1061/\(ASCE\)1084-0699\(1999\)4:3\(257\)](https://doi.org/10.1061/(ASCE)1084-0699(1999)4:3(257))
869

870 Mishra, S.K., Sahu, R.K., Eldho, T.I., & Jain, M.K., (2006). An improved I a S relation
871 incorporating antecedent moisture in SCS-CN methodology. *Water Resources Management*, 20(5),
872 643-660. <https://doi.org/10.1007/s11269-005-9000-4>
873

874 Mishra, S.K., & Singh, V.P., (2013). Soil conservation service curve number (SCS-CN)
875 methodology (Vol. 42). Springer Science & Business Media.
876

877 Mollenhauer, K., Taysun, A., & Frede, H.G., (2002). C-factors of the universal soil loss equation
878 for olive plantations in water Anatolia (central Egean region). *Journal of Plant Nutrition and Soil*
879 *Science*, 165, 313–319 [https://doi.org/10.1002/1522-2624\(200206\)165:3<313::AID-](https://doi.org/10.1002/1522-2624(200206)165:3<313::AID-JPLN313>3.0.CO;2-Q)
880 [JPLN313>3.0.CO;2-Q](https://doi.org/10.1002/1522-2624(200206)165:3<313::AID-JPLN313>3.0.CO;2-Q)
881

882 Montanarella, L., & Panagos, P. (2021). The relevance of sustainable soil management within the
883 European Green Deal. *Land Use Policy*, 100, 104950.
884 <https://doi.org/10.1016/j.landusepol.2020.104950>
885

886 Moreira Madueño J., (1991). Capacidad de uso y erosion de suelos: Una aproximacion a la
887 evaluacion de tierras en Andalucia. Agencia de Medio Ambiente Sevilla.
888

889 Morgan, R. P. C., Morgan, D. D. V., & Finney, H. J. (1984). A predictive model for the
890 assessment of soil erosion risk. *Journal of agricultural engineering research*, 30, 245-253.
891

892 Moriasi, D. N., Arnold, J. G., Van Liew, M. W., Bingner, R. L., Harmel, R. D., & Veith, T. L.,
893 (2007). Model evaluation guidelines for systematic quantification of accuracy in watershed
894 simulations. *Transactions of the ASABE*, 50(3), 885-900. <https://doi.org/10.13031/2013.23153>
895

896 Nash J.E. & Sutcliffe J.V., (1970). River flow forecasting through conceptual models. Part I. A
897 discussion of principles. *Journal of Hydrology*, 10: 282-290. [https://doi.org/10.1016/0022-](https://doi.org/10.1016/0022-1694(70)90255-6)
898 [1694\(70\)90255-6](https://doi.org/10.1016/0022-1694(70)90255-6)
899

- Nearing, M. A., (2000). Evaluating soil erosion models using measured plot data: accounting for variability in the data. *Earth Surface Processes and Landforms: The Journal of the British Geomorphological Research Group*, 25(9), 1035-1043. [https://doi.org/10.1002/1096-9837\(200008\)25:9<1035::AID-ESP121>3.0.CO;2-B](https://doi.org/10.1002/1096-9837(200008)25:9<1035::AID-ESP121>3.0.CO;2-B)
- Nekhay, O., Arriaza, M., & Boerboom, L., (2009). Evaluation of soil erosion risk using Analytic Network Process and GIS: A case study from Spanish mountain olive plantations. *Journal of Environmental Management*, 90(10), 3091-3104. <https://doi.org/10.1016/j.jenvman.2009.04.022>
- Noor, H., Mirnia, S.K., Fazli, S., Raisi, M.B., & Vafakhah, M., (2010). Application of MUSLE for the prediction of phosphorus losses. *Water Science and Technology*, 62(4). <https://doi.org/10.2166/wst.2010.092>
- Pan, C., Ma, L., & Shangguan, Z., (2010). Effectiveness of grass strips in trapping suspended sediments from runoff. *Earth Surface Processes and Landforms*, 35(9), 1006-1013.
- Panagos, P., Borrelli, P., Meusburger, C., Alewell, C., Lugato, E. & Montanarella, L., (2015). Estimating the soil erosion cover-management factor at European scale. *Land Use Policy*. 48C, 38-50 <https://doi.org/10.1016/j.landusepol.2015.05.021>
- Pardini, G.; Gispert, M. (2013) Soil quality assessment through a multi-approach analysis in soils of abandoned terraced land in NE Spain. *Cuad. Investigation in Geography.*, 38, 7–38.
- Polykretis, C., Alexakis, D.D., Grillakis, M.G., & Manoudakis, S., (2020). Assessment of intra-annual and inter-annual variabilities of soil erosion in Crete Island (Greece) by incorporating the Dynamic “Nature” of R and C-Factors in RUSLE modeling. *Remote Sensing*, 12(15), 2439.
- Ponce, V.M., & Hawkins, R.H., (1996). Runoff curve number: Has it reached maturity?. *Journal of hydrologic engineering*, 1(1), 11-19. [https://doi.org/10.1061/\(ASCE\)1084-0699\(1996\)1:1\(11\)](https://doi.org/10.1061/(ASCE)1084-0699(1996)1:1(11))
- Pongsai, S., Schmidt Vogt, D., Shrestha, R.P., Clemente, R.S., & Eiumnoh, A., (2010). Calibration and validation of the Modified Universal Soil Loss Equation for estimating sediment yield on sloping plots: A case study in Khun Satan catchment of northern Thailand. *Canadian journal of soil science*, 90(4), 585-596. <https://doi.org/10.4141/cjss09076>

934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967

Renard, K.G., Foster, G.R., Weesies, G.A. & Porter, J.P., (1991). RUSLE: revised universal soil loss equation. *Journal of Soil and Water Conservation*, 30-33 (January–February).

Risse, L.M., Nearing, M.A., Laflen, J.M., & Nicks, A.D., (1993). Error assessment in the universal soil loss equation. *Soil Science Society of America Journal*, 57, 825.
<https://doi.org/10.2136/sssaj1993.03615995005700030032x>

Rocha, G.C.D., & Sparovek, G., (2021). Scientific and technical knowledge of sugarcane cover-management USLE/RUSLE factor. *Scientia Agricola*, 78.

Romero, P., Castro, G., Gómez, J.A., & Fereres, E., (2007). Curve number values for olive orchards under different soil management. *Soil Science Society of America Journal*, 71(6), 1758-1769. <https://doi.org/10.2136/sssaj2007.0034>

Roskopf, C. M., Di Iorio, E., Circelli, L., Colombo, C., & Aucelli, P.P., (2020). Assessing spatial variability and erosion susceptibility of soils in hilly agricultural areas in Southern Italy. *International Soil and Water Conservation Research*, 8(4), 354-362.

Sadeghi, S. H. R., Gholami, L., Khaledi Darvishan, A., & Saeidi, P., (2014). A review of the application of the MUSLE model worldwide. *Hydrological Sciences Journal*, 59(2), 365-375.)
<https://doi.org/10.1080/02626667.2013.866239>

Santhi, C., Arnold, J.G., Williams, J.R., Dugas, W.A., Srinivasan, R., Hauck, L.M., (2001). Validation of the Swat model on a large River basin with point and nonpoint sources 1. *Journal of the American Water Resources Association* 37, 1169–1188.

Sastre, B., Marques, M. J., García-Díaz, A., & Bienes, R. (2018). Three years of management with cover crops protecting sloping olive groves soils, carbon and water effects on gypsiferous soil. *Catena*, 171, 115e124. <https://doi.org/10.1016/j.catena.2018.07.003>

Shen, Z.Y., Gong, Y.W., Li, Y.H., Hong, Q., Xu, L., & Liu, R.M., (2009). A comparison of WEPP and SWAT for modeling soil erosion of the Zhangjiachong Watershed in the Three Gorges Reservoir Area. *Agricultural Water Management*, 96(10), 1435-1442.
<https://doi.org/10.1016/j.agwat.2009.04.017>

968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

Singer, M. J., Matsuda, Y., & Blackard, J., (1981). Effect of mulch rate on soil loss by raindrop splash. *Soil Science Society of America Journal*, 45(1), 107-110.
<https://doi.org/10.2136/sssaj1981.03615995004500010023x>

Soulis, K.X., (2021). Soil Conservation Service Curve Number (SCS-CN) Method: Current Applications, Remaining Challenges, and Future Perspectives. *Water* 2021, 13, 192.

Suresh Babu, P., & Mishra, S.K., (2012). Improved SCS-CN–inspired model. *Journal of Hydrologic Engineering*, 17(11), 1164-1172. [https://doi.org/10.1061/\(ASCE\)HE.1943-5584.0000435](https://doi.org/10.1061/(ASCE)HE.1943-5584.0000435)

Taguas, E.V., Yuan, Y., Bingner, R.L., & Gomez, J.A., (2012). Modeling the contribution of ephemeral gully erosion under different soil managements: A case study in an olive orchard microcatchment using the AnnAGNPS model. *Catena*, 98, 1-16.
<https://doi.org/10.1016/j.catena.2012.06.002>

Taguas, E.V., Yuan, Y., Licciardello, F., & Gómez, J.A., (2015). Curve numbers for olive orchard catchments: Case study in Southern Spain. *Journal of Irrigation and Drainage Engineering*, 141(11), 05015003. [http://dx.doi.org/10.1061/\(ASCE\)IR.1943-4774.0000892](http://dx.doi.org/10.1061/(ASCE)IR.1943-4774.0000892)

Taguas, E.V., Gómez, J.A., Denisi, P., & Mateos, L., (2015b). Modelling the rainfall-runoff relationships in a large olive orchard catchment in southern Spain. *Water Resources Management*, 29(7), 2361-2375.

USDA, Soil Conservation Service, (1972). National Engineering Handbook, *Hydrology*, Section 4: 548. Washington D.C.: USDA Soil Conservation Service.

Uwizeyimana, D., Mureithi, S.M., Mvuyekure, S.M., Karuku, G., & Kironchi, G., (2019). Modelling surface runoff using the soil conservation service-curve number method in a drought prone agro-ecological zone in Rwanda. *International Soil and Water Conservation Research*, 7(1), 9-17. <https://doi.org/10.1016/j.iswcr.2018.12.001>

1001 Van Liew, M.W., Arnold, J.G., Garbrecht, J.D., (2003). Hydrologic simulation on agricultural
1002 watersheds: Choosing between two models. *Transactions of the ASAE* 46, 1539.
1003 <https://doi.org/10.13031/2013.15643>) @2003
1004

1005 Van Liew, M.W., & Garbrecht, J., (2003). Hydrologic simulation of the little Washita river
1006 experimental watershed using SWAT. *Journal of the American Water Resources Association*,
1007 39(2), 413-426. <https://doi.org/10.1111/j.1752-1688.2003.tb04395.x>
1008

1009 Van Oost, K., Govers, G., & Desmet, P. (2000). Evaluating the effects of changes in landscape
1010 structure on soil erosion by water and tillage. *Landscape ecology*, 15(6), 577-589.
1011

1012 Vanwalleghe, T., Laguna, A., Giráldez, J. V., & Jiménez-Hornero, F. J. (2010). Applying a
1013 simple methodology to assess historical soil erosion in olive orchards. *Geomorphology*, 114(3),
1014 294-302. <https://doi.org/10.1016/j.geomorph.2009.07.010>
1015

1016 Vanwalleghe, T., Amate, J.I., de Molina, M.G., Fernández, D.S., & Gómez, J.A., (2011).
1017 Quantifying the effect of historical soil management on soil erosion rates in Mediterranean olive
1018 orchards. *Agriculture, ecosystems & environment*, 142(3-4), 341-351.
1019 <https://doi.org/10.1016/j.agee.2011.06.003>
1020

1021 Vieira, D.C.S., Serpa, D., Nunes, J.P.C., Prats, S.A., Neves, R., Keizer, J.J., (2018a). Predicting the
1022 effectiveness of different mulching techniques in reducing post-fire runoff and erosion at plot scale
1023 with the RUSLE, MMF and PESERA models. *Environmental Research* 165, 365–378.
1024 <https://doi.org/10.1016/j.envres.2018.04.029>.
1025

1026 Williams, J.R., (1975) Sediment-Yield Prediction with Universal Equation Using Runoff Energy
1027 Factor; ARS-S. Southern Region, Agricultural Research Service, US Department of Agriculture:
1028 Washington, DC, USA; Volume 40, p. 244.
1029

1030 Williams, J. R., (1977). *Sediment delivery ratios determined with sediment and runoff models*.
1031 IAHS Publ, 122, 168-179.
1032

Williams, J. R., (1982). Testing the modified universal soil loss equation. In Proceedings of the Workshop on Estimating Erosion and Sediment Yield on Rangelands, Tucson, Arizona March 7-9, 1981, *Agricultural Reviews and Manuals* ARM-W-26, June 1982, p 157-165.

Wischmeier, W.H., & Smith, D.D., (1978). Predicting rainfall erosion losses: a guide to conservation planning (No. 537). Department of Agriculture, Science and Education Administration..

Xiloyannis, C., Raya, A. M., Kosmas, C., & Favia, M. (2008). Semi-intensive olive orchards on sloping land: Requiring good land husbandry for future development. *Journal of Environmental Management*, 89(2), 110-119.

Yu, B., (1998). Theoretical justification of SCS method for runoff estimation. *Journal of irrigation and drainage engineering*, 124(6), 306-310.

Zema, D. A., Denisi, P., Taguas Ruiz, E. V., Gómez, J. A., Bombino, G., & Fortugno, D. (2016). Evaluation of surface runoff prediction by a nn AGNPS model in a large Mediterranean watershed covered by olive groves. *Land degradation & development*, 27(3), 811-822.

Zema D.A., Lucas-Borja M.E., Carrà B.G., Denisi P., Rodrigues V.A., Ranzini M., Soriano F.C., de Cicco V., Zimbone S.M., (2018). Simulating the hydrological response of a small tropical forest watershed (Mata Atlantica, Brazil) by the AnnAGNPS model. *Science of The Total Environment*, 636: 737-750. <https://doi.org/10.1016/j.scitotenv.2018.04.339>

Zema, D.A., Lucas-Borja, M.E., Andiloro, S., Tamburino, V., & Zimbone, S.M., (2019). Short-term effects of olive mill wastewater application on the hydrological and physico-chemical properties of a loamy soil. *Agricultural Water Management*, 221, 312-321. <https://doi.org/10.1016/j.agwat.2019.04.011>

Zema, D.A., Nunes, J.P., & Lucas-Borja, M.E., (2020a). Improvement of seasonal runoff and soil loss predictions by the MMF (Morgan-Morgan-Finney) model after wildfire and soil treatment in Mediterranean forest ecosystems. *Catena*, 188, 104415.